

Angular Contact Bearing

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
7000C	10	26	8	5.3	2.45	47000	62000	0.021
7000AC	10	26	8	5	2.35	34000	42000	0.021
7200C	10	30	9	5	2.35	40000	54000	0.031
7200AC	10	30	9	4.65	2.2	29000	37000	0.031
7001C	12	28	8	5.8	2.95	40000	54000	0.024
7001AC	12	28	8	5.4	2.75	29000	37000	0.024
7201C	12	32	10	7.9	3.85	38000	50000	0.038
7201AC	12	32	10	7.45	3.65	27000	34000	0.038
7002C	15	32	9	6.6	3.7	35000	47000	0.035
7002AC	15	32	9	6.1	3.45	26000	32000	0.035
7202C	15	35	11	8065	4.55	33000	43000	0.048
7202AC	15	35	11	8.1	4.25	24000	29000	0.048
7003C	17	35	10	7.3	4.45	31000	41000	0.045
7003AC	17	35	10	6.75	4.15	23000	28000	0.045
7203C	17	40	12	10.9	5.9	29000	38000	0.07
7203AC	17	40	12	10.2	5.5	21000	26000	0.07
7004C	20	42	12	11.1	6.6	26000	35000	0.079
7004AC	20	42	12	10.3	6.1	19000	24000	0.079
7204C	20	47	14	15.5	9	24000	32000	0.112
7204AC	20	47	14	14.5	8.4	17000	22000	0.112
7204B	20	47	14	13.3	7.7	13000	17000	0.112
7005C	25	47	12	12.3	8	23000	30000	0.091
7005AC	25	47	12	11.3	7.4	17000	21000	0.091
7205C	25	52	15	16.6	10.2	21000	28000	0.135
7205AC	25	52	15	15.3	9.5	15000	19000	0.135
7205B	25	52	15	14	8.7	12000	15000	0.135
7305B	25	62	17	22.9	13.3	10000	14000	0.243
7006C	30	55	13	15.8	11	20000	26000	0.133
7006AC	30	55	13	14.5	10.1	14000	18000	0.133
7206C	30	62	16	23	14.7	18000	24000	0.208
7206AC	30	62	16	21.3	13.7	13000	16000	0.208
7206B	30	62	16	19.4	12.5	9600	13000	0.208
7306B	30	72	19	27.6	17.4	8700	12000	0.362
7007C	35	62	14	19.1	13.7	17000	22000	0.17
7007AC	35	62	14	17.5	12.6	12000	15000	0.17
7207C	35	72	17	30.4	20.1	15000	20000	0.295
7207AC	35	72	17	28.1	18.6	11000	14000	0.295
7207B	35	72	17	25.6	17	8300	11000	0.295
7307B	35	80	21	32.5	20.2	7700	10000	0.475
7008C	40	68	15	20.5	15.9	15000	20000	0.21
7008AC	40	68	15	18.7	14.6	11000	14000	0.21
7208C	40	80	18	36.4	25.2	14000	18000	0.382
7208AC	40	80	18	33.6	23.3	10000	12000	0.382
7208B	40	80	18	30.6	21.3	7500	10000	0.382

瓦房店金锐轴承制造有限公司

Wafangdian Jinrui Bearing manufacturing Co., Ltd

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
7215B	75	130	25	71.7	59.3	4300	5800	1.23
7915B	75	160	37	125	98.5	3400	4500	3.3
7016C	80	125	22	58.7	55.3	8000	11000	0.93
7016AC	80	125	22	53.4	50.6	5800	7200	0.93
7216C	80	140	26	92.8	77.5	7500	9900	1.5
7216AC	80	140	26	85.3	71.5	5400	6700	1.5
7216B	80	140	26	77.1	65	4000	5400	1.5
7316B	80	170	39	127	100	3500	4700	3.85
7017C	85	130	22	60.1	58.7	7600	10000	0.97
7017AC	85	130	22	54.6	53.7	5500	6800	0.97
7217C	85	150	28	107	90.6	7000	9200	1.87
7217AC	85	150	28	98.6	83.6	5000	6300	1.87
7217B	85	150	28	89.2	76	3800	5000	1.87
7317B	85	180	41	137	112	3300	4400	4.53
7018C	90	140	24	71.7	69.1	7100	9400	1.26
7018AC	90	140	24	65.2	63.3	5100	6400	1.26
7218C	90	160	30	123	105	6500	8600	2.3
7218AC	90	160	30	113	96.7	4700	5900	2.3
7218B	90	160	30	102	88	3500	4700	2.3
7318B	90	190	43	148	124	3100	4200	5.3
7019C	95	145	24	73.4	73.4	6700	8900	1.32
7019AC	95	145	24	66.6	67.1	4800	6000	1.32
7219C	95	170	32	133	112	6100	8100	2.78
7219AC	95	170	32	122	103	4400	5500	2.78
7219B	95	170	32	111	94	3300	4400	2.78
7319B	95	200	45	158	137	3000	4000	6.12
7020C	100	150	24	75.3	77.2	6500	8600	1.37
7020AC	100	150	24	68.4	70.6	4700	5900	1.37
7220C	100	180	34	149	127	5700	7600	3.32
7220AC	100	180	34	137	117	4100	5200	3.32
7220B	100	180	34	124	107	3100	4200	3.32
7320B	100	215	47	168	148	2700	3600	7.53
7021C	105	160	26	87.8	89.6	6000	8000	1.73
7021AC	105	160	26	79.8	81.9	4400	5500	1.73
7221C	105	190	36	162	143	5400	7200	3.95
7221AC	105	190	36	149	132	3900	4900	3.95
7221B	105	190	36	135	121	2900	3900	3.95
7321B	105	225	49	191	177	2600	3500	8.62
7022C	110	170	28	101	101	5800	7700	2.14
7022AC	110	170	28	91.9	92.8	4200	5200	2.14
7222C	110	200	38	176	160	5100	6800	4.65
7222AC	110	200	38	162	148	3700	4600	4.65
7222B	110	200	38	147	135	2800	3700	4.65
7322B	110	240	50	213	208	2400	3200	10.1

瓦房店金锐轴承制造有限公司

Wafangdian Jinrui Bearing manufacturing Co., Ltd

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
7308B	40	90	23	39.7	25.2	6900	9200	0.657
7408B	40	110	27	64.9	40.4	5200	7200	1.23
7009C	45	75	16	24.4	19.3	14000	18000	0.26
7009AC	45	75	16	22.2	17.7	100000	12000	0.26
7209C	45	85	19	40.8	28.7	13000	17000	0.43
7209AC	45	85	19	37.7	26.6	9400	12000	0.43
7209B	45	85	19	34.3	24.3	7000	9400	0.43
7309B	45	100	25	50.6	34.1	6200	8200	0.875
7010C	50	80	16	26	21.9	13000	17000	0.29
7010AC	50	80	16	23.6	20.1	9200	11000	0.29
7210C	50	90	20	42.8	31.8	12000	16000	0.485
7210AC	50	90	20	39.4	41.3	8500	11000	0.485
7210B	50	90	20	37.535.7	26.7	6400	8500	0.485
7310B	50	110	27	64.4	44.3	5500	7300	1.14
7410B	50	130	31	90.2	60.4	4400	6000	1.92
7011C	55	90	18	34.1	28.6	11000	15000	0.42
7011AC	55	90	18	31.1	26.3	8300	10000	0.42
7211C	55	100	21	52.9	40.2	11000	14000	0.635
7211AC	55	100	21	48.7	37.1	7600	9500	0.635
7211B	55	100	21	44.1	33.8	5700	7600	0.635
7311B	55	120	29	74.3	52	5000	6700	1.45
7012C	60	95	18	35	30.6	11000	14000	0.45
7012AC	60	95	18	31.9	28.1	7700	9700	0.45
7212C	60	110	22	64	49.5	9500	13000	0.82
7212AC	60	110	22	58.9	45.7	6900	8600	0.82
7212B	60	110	22	53.4	41.6	5100	6900	0.82
7312B	60	130	31	84.9	60.3	4600	6200	1.81
7412B	60	150	35	119	86.7	3700	5100	2.85
7013C	65	100	18	37.1	34.3	10000	13000	0.47
7013AC	65	100	18	33.7	31.4	7200	9000	0.47
7213C	65	120	23	73.1	58.7	8900	12000	1.02
7213AC	65	120	23	67.3	54.2	6400	8000	1.02
7213B	65	120	23	60.9	49.3	4800	6400	1.02
7313B	65	140	33	96.1	69.3	4300	5800	2.22
7014C	70	110	20	46.9	43	9200	12000	0.66
7014AC	70	110	20	42.7	39.4	6600	8300	0.66
7214C	70	125	24	75.9	60.2	8400	11000	1.12
7214AC	70	125	24	69.8	55.6	6100	7600	1.12
7214B	70	125	24	63.2	50.6	4600	6100	1.12
7314B	70	150	35	108	78.9	4000	5400	2.7
7015C	75	115	20	48	45.6	8700	11000	0.69
7015AC	75	115	20	43.6	41.7	6300	7800	0.69
7215C	75	130	25	86.1	70.6	8000	11000	1.23
7215AC	75	130	25	79.2	65.2	5800	7200	1.23

瓦房店金锐轴承制造有限公司

Wafangdian Jinrui Bearing manufacturing Co., Ltd

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
S7001J	12	28	8	2.3	2.68	18000	26000	-
S78201J	12	32	7	2.5	3	17000	24000	0.028
S7002J	15	32	9	2.5	3.68	17000	24000	0.028
S78202J	15	35	8	3.3	4.00	16000	22000	0.035
SN7202J	15	35	11	6.7	4.5	16000	22000	0.0436
S7202J	15	35	11	3.7	4.5	16000	22000	0.044
SN7203J	17	40	12	9.2	6.45	15000	20000	0.0596
S7004J	20	42	12	3.8	4.92	14000	19000	0.065
SN7204J	20	47	14	10.1	8.05	13000	18000	0.0946
SN7205J	25	52	15	12.8	9.55	11000	16000	0.114
SN7206J	30	62	16	17.8	14.8	9000	13000	0.187
S718/600	600	730	60	332	888	380	500	60.7
S718/800	800	980	82	568	1890	200	300	132
S718/1180	1180	1420	106	850	3580	-	-	332
3200	10	30	14.3	7.35	5.35	15000	20000	0.052
3201	12	32	15.9	9.7	7.15	14000	18000	0.063
3202	15	35	15.9	9.7	7.45	12000	16000	0.072
3203	17	40	17.5	13.8	10.8	11000	14000	0.1
3204	20	47	20.6	17.2	15	9000	12000	0.17
3304	20	52	22.2	20.8	18.4	8200	11000	0.23
3205	25	52	20.6	18.9	18.2	7800	10000	0.19
3305	25	62	25.4	28.9	26.5	6800	9100	0.369
3206	30	62	23.8	27.3	27	6500	8700	0.32
3306	30	72	30.2	38.1	36.1	5800	7800	0.585
3207	35	72	27	36.8	37.5	5600	7500	0.48
3307	35	80	34.9	48.6	46.8	5200	7000	0.816
3208	40	80	30.2	42	43.9	5000	6700	0.65
3308	40	90	36.5	54.1	53.8	4600	6100	1.07
3209	45	85	30.2	45.4	51.4	4600	6100	0.71
3309	45	100	39.7	66.1	67.3	4100	5500	1.42
3210	50	90	30.2	45.1	52.1	4300	5700	0.76
3310	50	110	44.4	86.1	88.6	3800	5000	1.95
3211	55	100	33.3	50.9	60.2	3900	5100	1.05
3311	55	120	49.2	101	106	3400	4500	2.53
3212	60	110	36.5	64	76.8	3500	4700	1.4
3312	60	130	54	125	132	3100	4200	3.24
3213	65	120	38.1	76.4	97.4	3200	4300	1.75
3313	65	140	58.7	142	153	2900	3900	4.08
3214	70	126	39.7	77.9	96.4	3100	4100	1.92
3314	70	150	63.5	151	160	2700	3600	5.04
3215	75	130	41.3	82	115	3200	4300	2.09
3315	75	160	68.3	156	191	3000	4100	6.27
3216	80	140	44.4	97.5	121	2700	3600	2.64
3316	80	170	68.3	184	213	2400	3100	6.93

瓦房店金锐轴承制造有限公司

Wafangdian Jinrui Bearing manufacturing Co., Ltd

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com