



Bearing type	Internal Diameter	Outer Diameter	Width	Dynamic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	W	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
292/1060	1060	1400	206	-	-	-	-	-
29230	150	215	39	-	-	-	-	-
29232	160	225	39	-	-	-	-	-
29234	170	240	42	-	-	-	-	-
29240	200	280	48	536	2270	1600	-	8.9
29244	220	300	48	542	2490	1550	-	10
29248	240	340	60	822	3680	1250	-	16.7
29252	260	360	60	838	3720	1200	-	18.5
29264	320	440	73	1110	5170	900	-	32.9
29272	360	500	85	1460	6450	750	-	51.8
29276	380	520	85	1580	7430	700	-	52.8
29284	420	580	95	1990	9620	600	-	75.4
29288	440	600	95	2060	9830	600	-	77.9
29292	460	620	95	2150	10200	550	-	81
29296	480	650	103	2350	11600	500	-	89
29317	85	150	39	287	927	2600	-	2.82
29334	170	280	67	880	3170	1350	-	16.2
29336	180	300	73	1030	3730	1250	-	20.7
29364	320	500	109	2310	9380	650	-	78
29368	340	540	122	2700	10730	600	-	106
29376	380	600	132	3380	13900	500	-	141
29384	420	650	140	3610	14900	450	-	172
29388	440	680	145	4000	16400	420	-	182
29396	480	730	150	4390	18600	390	-	218
292/500	500	670	103	2460	14800	500	-	101
292/530	530	710	109	2800	16200	400	-	108
292/670	670	900	140	4440	26500	200	-	224
292/710	710	950	145	4840	29400	150	-	261
292/750	750	1000	150	5180	31900	130	-	293
292/800	800	1060	155	5620	35300	100	-	339
292/850	850	1120	160	6080	38900	80	-	389
292/900	900	1180	170	6590	42000	60	-	444
292/950	950	1250	180	-	-	-	-	-
293/500	500	750	150	4510	19700	380	-	233
293/530	530	800	160	5170	26300	320	-	270
293/560	560	850	175	5790	29700	280	-	320
293/600	600	900	180	6350	32600	250	-	368
293/630	630	950	190	7070	37000	200	-	438
293/670	670	1000	200	7720	40300	150	-	501
293/710	710	1060	212	8570	45100	120	-	591
293/750	750	1120	224	9370	50600	100	-	696
293/800	800	1180	230	10110	54900	80	-	785
293/850	850	1250	243	-	-	-	-	-

293/900	900	1320	250	-	-	-	-	-
---------	-----	------	-----	---	---	---	---	---

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	W	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
28334	170	290	73	—	—	—	—	15
29236	180	250	42	—	—	—	—	7.5
29238	190	270	48	—	—	—	—	8
29256	280	380	60	862	4020	1150	—	19.5
29260	300	420	73	1070	4890	950	—	30.5
29268	340	460	73	1150	5300	900	-	33.6
29280	400	540	85	1610	7850	700	—	55.3
29318	90	155	30	299	966	2500	-	3.06
29320	100	170	42	355	1160	2300	—	3.81
29322	110	190	48	457	1530	2000	-	5.56
29324	120	210	54	553	1880	1800	—	7.63
29326	130	225	58	643	2220	1700	—	9.43
29328	140	240	60	707	2490	1600	-	11.1
29330	150	250	60	711	2500	1550	—	11.6
29332	160	270	67	862	3070	1400	—	15.4
81140	200	250	37	385	1500	—	—	2.23
81188	440	540	80	—	—	—	—	2.23
81210	50	78	22	117	315	—	3700	0.356
81213	65	100	27	—	—	—	—	0.87
81215	75	110	27	172	500	-	2600	0.8
81217	85	125	31	217	660	-	2300	1.26
81222	110	160	38	300	840	-	1800	2.445
292244	220	300	48	—	—	—	—	9.84
292/560	560	750	115	3090	18100	350	—	140
292/600	600	800	122	3420	20100	300	—	172
292/630	630	850	132	4030	23900	250	—	218
29238E	190	270	48	—	—	—	—	8
29326E	130	225	58	—	—	—	—	8.17
811/1320	1320	1540	175	—	—	—	—	480
81124/P4	120	155	25	—	—	—	—	1.36
81124/P5	120	155	25	—	—	—	—	1.36
81208/P6	40	68	19	—	—	—	—	0.32
871/1180ZW	1180	1400	100	—	—	—	—	311
872/5302ZW/PS	530	710	82	—	—	—	—	89.6
872/670ZW/P5	670	900	103	—	—	—	—	198
872/900ZW	900	1180	125	—	—	—	—	386
89311ZW/P5	55	105	30	—	—	—	—	1.38
89317ZW/P5	85	150	39	—	—	—	—	3.35
89320ZW/P5	100	170	42	—	—	—	—	4.49
91208ZSV/YA	47.1	70	22	—	—	—	—	0.292

91235X2	180	250	58	—	—	—	—	7.85
AXK160200	160	200	5	12.8	992	1200	—	0.215
KLW-81130/P4	150	190	21.5	—	—	—	—	1.52
KLW-81136/P4	180	225	24	—	—	—	—	2.23

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	W	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
8110	50	70	14	—	—	—	—	0.0228
8111	55	78	16	—	—	—	—	0.27
8117	85	110	19	—	—	—	—	0.52
29416	80	170	54	468	1380	2000	-	5.91
29440	200	400	122	2250	7580	800	-	72.2
29460	300	540	145	3360	12000	550	-	142
29480	400	710	185	5630	21900	380	-	309
29484	420	730	185	5750	22500	370	-	326
29488	440	780	206	6600	26000	320	-	411
29492	460	800	206	6880	27900	300	-	425
29496	480	850	224	7840	31000	270	-	550
81102	15	28	9	14.4	28.5	-	11000	0.024
81113	65	90	18	107	340	-	3100	0.31
294/500	500	870	224	8000	32300	270	-	560
294/530	530	920	236	9000	41600	300	-	650
294/560	560	980	250	10210	47800	250	-	740
294/600	600	1030	258	-	-	-	-	-
294/630	630	1090	280	-	-	-	-	-
294/670	670	1150	290	-	-	-	-	-
294/710	710	1220	308	-	-	-	-	-
294/750	750	1280	315	-	-	-	-	-
294/800	800	1360	335	-	-	-	-	-
81108/P4	40	60	13	—	—	—	—	0.15
81112/P4	60	85	17	—	—	—	—	0.34
8118/P4	90	120	82	—	—	—	—	0.8
AXK110145	110	145	4	91	598	1800	—	0.109
AXK120155	120	155	4	100	630	1600	—	0.113
AXK1226	12	26	2	9	24	12000	—	0.003
AXK1528	15	28	2	10.03	31.2	9900	—	0.017
AXK1730	17	30	2	10.8	35	9000	—	0.02
AXK1730TN1	17	30	2	—	—	—	—	0.017
AXK2035	20	35	2	11.1	43	8000	—	0.0058
AXK2542	25	42	2	12.5	52	6500	—	0.01
AXK3047	30	47	2	13.5	63	5100	—	0.01
AXK3552	35	52	2	14.9	75	5000	—	0.0125
AXK4060	40	60	3	25	102	4200	—	0.0125
AXK4565	45	65	3	24	108	4000	—	0.0228
AXK5070	50	70	3	29.9	121	—	—	0.0235

AXK5578	55	78	3	34	166	3200	—	0.04
AXK6085	60	85	3	41.2	214	3000	—	0.04
AXK6590	65	90	3	41.5	232	2800	—	0.0426
AXK75100	75	100	4	51	227	2400	—	0.455
AXK80105	80	105	4	52	240	2500	—	0.05
AZK1024	10	24	2	—	—	—	—	17

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	W	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
39336	180	300	73	—	—	—	—	18.3
29338	190	320	78	1170	4230	1150	—	25.1
29340	200	240	85	1360	5040	1050	—	31.2
29344	220	360	85	1380	5240	1000	-	33.3
29348	240	380	85	1410	5500	950	—	35.5
29352	260	420	95	1810	6950	850	—	49.1
29356	280	440	95	1840	7150	800	—	53.2
29360	300	480	109	2250	8790	700	—	74.9
29372	360	560	132	2760	11300	550	—	110
29380	400	620	132	3440	14200	500	—	152
29392	460	710	150	4290	18000	400	—	216
29412	60	130	42	293	854	2700	—	2.61
29413	65	140	45	344	1000	2500	—	3.34
29414	70	150	48	378	1110	2300	—	4.06
29415	75	160	51	438	1270	2100	—	4.76
29417	85	180	58	536	1610	1900	—	7.04
29418	90	160	60	598	1810	1800	—	8.18
29420	100	210	67	722	2220	1650	—	11.2
29422	110	230	73	845	2610	1500	—	14.7
29424	120	350	78	975	3080	1350	—	18.2
29426	130	270	85	1130	3530	1250	—	22.8
29428	140	280	85	1170	3790	1250	—	24.6
29430	150	300	90	1330	4320	1100	—	29.9
29432	160	320	95	1480	4860	1050	—	36.2
29434	170	340	103	1640	5340	950	—	44.3
29436	180	360	109	1870	6110	900	-	52.6
29438	190	380	115	2040	6730	850	—	60.7
29444	220	420	122	2300	7910	750	—	74.9
29448	240	440	122	2390	8500	700	—	80
29452	260	480	132	2870	10400	650	—	104
87436	180	360	82	—	—	—	—	95.7
89448	240	440	122	3000	12200	-	400	87.8
99440	200	400	122	—	—	—	—	75
99452	260	480	132	—	—	—	—	111
29352D	260	420	95	—	—	—	—	57.1

29352E	260	420	95	—	—	—	—	53.6
29352M	260	420	95	—	—	—	—	49.5
29418/YA	90	160	60	—	—	—	—	7.6
29434E	170	340	103	—	—	—	—	40.7
29438ME	190	380	115	—	—	—	—	63.94
87412/P5	60	130	32	—	—	—	—	2.45
99436Q1	180	360	109	—	—	—	—	67.2
99440ME	200	400	122	—	—	—	—	68.61
99440Q1	200	400	122	—	—	—	—	75

瓦房店金锐轴承制造有限公司

Wafangdian Jinrui Bearing manufacturing Co., Ltd

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com