



Bearing type	Internal Diameter	Outer Diameter	Width	Dynamic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D				Cr	Cor	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
22206	30	62	20	30.5	38.2	5300	6700	0.28
22207	35	72	23	45.2	59.5	4800	6000	0.43
22208	40	80	23	49.8	68.5	4500	5600	0.55
22209	45	85	23	52	73	4000	5000	0.59
22210	50	90	23	52	73	3800	4800	0.61
22211	55	100	25	60	87	3400	4300	0.85
22212	60	110	28	82	122	3200	4000	1.22
22213	65	120	31	89	128	2800	3600	1.63
22214	70	125	31	95	142	2600	3400	1.66
22215	75	130	31	95	142	2400	3200	1.75
22216	80	140	33	115	180	2200	3000	2.20
22217	85	150	36	145	228	2000	2800	2.80
22218	90	160	40	168	272	1900	2600	4.00
22219	95	170	43	212	322	1800	2400	4.20
22220	100	180	46	222	358	1700	2200	5.00
22222	110	200	53	288	465	1500	1900	7.40
22224	120	215	58	342	565	1300	1700	9.20
22226	130	230	64	408	708	1200	1600	11.20
22228	140	250	68	478	805	1000	1400	14.50
22230	150	270	73	508	875	950	1300	18.50
22232	160	290	80	642	1140	900	1200	22.20
22234	170	310	86	720	1300	850	1100	29.00
22236	180	320	86	735	1370	800	1000	30.00
22238	190	340	92	818	1510	750	950	35.30
22240	200	360	98	920	1740	700	900	47.70
22244	220	400	108	1170	2220	630	800	61.50
22256	280	500	130	1690	3380	500	630	126.00
22260	300	540	140	1840	3450	450	560	134.00

Bearing type	Internal Diameter	Outer Diameter	Width	Dynamic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D				Cr	Cor	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
22310	50	110	40	128	170	3400	4300	1.90
22311	55	120	43	155	198	3000	3800	2.40
22312	60	130	46	168	225	2800	3600	3.00
22313	65	140	48	188	252	2400	3200	3.60
22314	70	150	51	230	315	2200	3000	4.40
22315	75	160	55	262	388	2000	2800	5.40
22316	80	170	58	288	405	1900	2600	6.40
22317	85	180	60	308	440	1800	2400	7.40
22318	90	190	64	365	542	1700	2200	8.80

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com

22319	95	200	67	385	570	1600	2000	10.30
22320	100	215	73	450	668	1400	1800	13.00
22322	110	240	80	545	832	1200	1600	18.10
22324	120	260	86	645	992	1100	1500	22.00
22326	130	280	93	722	1140	950	1300	29.00
22328	140	300	102	825	1340	900	1200	36.00
22330	150	320	108	1020	1740	850	1100	43.00
22332	160	340	114	1040	1770	800	1000	51.00
22334	170	360	120	1150	2060	750	950	60.00
22336	180	380	126	1260	2270	700	900	70.00
22338	190	400	132	1390	2530	670	850	81.00
22340	200	420	138	1490	2720	630	800	94.00
22348	240	500	155	1730	3250	500	630	153.00
22352	260	540	165	2200	4190	480	600	191.00
22356	280	580	175	2420	4650	450	560	238.00

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	
23020	100	150	37	2400	400	215	3200	2.51
23022	110	170	45	195	410	1400	1800	3.90
23024	120	180	46	212	470	1200	1600	4.30
23026	130	200	52	270	608	1100	1500	6.20
23028	140	210	53	285	635	950	1.3	6.70
23030	150	225	56	328	768	900	1200	8.14
23032	160	240	60	368	825	850	1100	10.00
23034	170	260	67	445	1010	800	1000	13.00
23036	180	280	74	540	1230	750	950	17.60
23038	190	290	75	555	1230	700	900	20.00
23040	200	310	82	580	1310	670	850	24.00
23044	220	340	90	760	1810	600	750	28.80
23048	240	360	92	792	2060	530	670	35.50
23052	260	400	104	1000	2450	500	630	51.50
23056	280	420	106	1080	2680	450	560	62.00
23060	300	460	118	1260	3070	430	530	75.20
23064	320	480	121	1380	3260	400	500	81.50
23068	340	520	133	1580	3810	380	480	109.00
23072	360	540	134	1710	4180	360	450	114.00
23076	380	560	135	1710	4240	340	430	120.00
23080	400	600	148	2060	5110	300	380	154.00
23084	420	620	150	2060	5110	280	360	160.00
23088	440	650	157	2170	5740	260	340	192.00
23092	460	680	163	2460	6670	220	300	232.00

23096	480	700	165	2500	6440	200	280	232.00
230/500	500	720	167	2700	7180	190	260	235.00
230/530	530	780	185	3180	8310	170	220	304.00
230/560	560	820	195	3490	9950	160	200	364.00
230/600	600	870	200	3760	10400	130	170	417.00
230/630	630	920	212	4170	11500	120	160	511.00

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
23122	110	180	56	290	572	1100	1500	3.10
23126	130	210	64	398	605	950	1300	9.50
23128	140	225	68	512	1080	850	1100	10.90
23130	150	250	80	520	1110	800	1000	16.10
23134	170	280	88	695	1480	750	900	22.00
23136	180	300	96	788	1830	670	850	27.10
23138	190	320	104	910	2010	630	800	35.30
23140	200	340	112	1030	2350	600	750	50.70
23144	220	370	120	1200	2830	500	630	55.00
23148	240	400	128	1430	3320	450	560	55.50
23152	260	440	144	1590	3630	430	530	95.30
23156	280	460	146	1940	4420	400	500	103.00
23172	360	600	192	2620	6240	300	380	222.00
23188	440	720	226	3920	9190	190	260	420.00

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
23218	90	160	52	-	-	-	-	4.64
23220	100	180	60	-	-	-	-	6.38
23222	110	200	70	-	-	-	-	9.67
23224	120	215	76	-	-	-	-	9.50
23226	130	230	80	-	-	-	-	11.80
23228	140	250	88	-	-	-	-	15.80
23230	150	270	96	-	-	-	-	19.60
23232	160	290	104	-	-	-	-	36.10
23234	170	310	110	-	-	-	-	37.10
23236	180	320	112	-	-	-	-	40.00

23238	190	340	120	-	-	-	-	38.60
23240	200	360	128	-	-	-	-	51.00
23244	220	400	144	-	-	-	-	92.20
23248	240	440	160	-	-	-	-	127.00
23252	260	480	174	-	-	-	-	151.00
23256	280	500	176	-	-	-	-	153.00
23260	300	540	192	-	-	-	-	146.00
23264	320	580	208	-	-	-	-	260.00
23268	340	620	224	-	-	-	-	310.00
23272	360	650	232	-	-	-	-	330.00
23280	400	720	256	-	-	-	-	530.00
23284	420	760	272	-	-	-	-	535.00
23288	440	790	280	-	-	-	-	607.00
23292	460	830	296	-	-	-	-	717.00
23296	480	870	310	-	-	-	-	837.00
232/500	500	920	336	-	-	-	-	985.00
232/530	530	980	355	-	-	-	-	1200.00
232/560	560	1030	365	-	-	-	-	1350.00
232/60	600	1090	388	-	-	-	-	1600.00
232/670	670	1220	438	-	-	-	-	1780.00
232/750	750	1360	475	-	-	-	-	1820.00

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
23936	180	250	52	-	-	-	-	8
23938	190	260	52	-	-	-	-	8
23940	200	280	60	-	-	-	-	12
23948	240	320	60	-	-	-	-	15
23948	240	320	60	-	-	-	-	15
23952	260	360	75	-	-	-	-	22
23956	280	380	75	-	-	-	-	25
23960	300	420	90	-	-	-	-	41
23964	320	440	90	-	-	-	-	45
23968	340	460	90	-	-	-	-	48
23972	360	480	90	-	-	-	-	49
23976	380	520	106	-	-	-	-	74
23980	400	540	106	-	-	-	-	71
23984	420	560	106	-	-	-	-	73
23988	440	600	118	-	-	-	-	100
23992	460	620	118	-	-	-	-	101

23996	480	650	128	-	-	-	-	74
239/500	500	670	128	-	-	-	-	135
239/530	530	710	136	-	-	-	-	159
239/560	560	750	140	-	-	-	-	183
239/600	600	800	150	-	-	-	-	221
239/630	630	850	165	-	-	-	-	280
239/670	670	900	170	-	-	-	-	326
239/710	710	950	180	-	-	-	-	387
239/750	750	1000	185	-	-	-	-	395
239/800C	800	1060	195	-	-	-	-	506
239/850	850	1120	200	-	-	-	-	542
239/900C	900	1180	206	-	-	-	-	649
239/950C	950	1250	224	-	-	-	-	776

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	(kg)
24015	75	115	40	-	-	-	-	1.42
24018	90	140	50	-	-	-	-	2.92
24020	100	150	50	-	-	-	-	3.20
24022	110	170	60	-	-	-	-	5.12
24024	120	180	60	-	-	-	-	5.11
24026	130	200	69	-	-	-	-	7.95
24028	140	210	69	-	-	-	-	8.09
24030	150	225	75	-	-	-	-	9.45
24032	160	240	80	-	-	-	-	12.30
24034	170	260	90	-	-	-	-	12.90
24036	180	280	100	-	-	-	-	22.50
24038	190	290	100	-	-	-	-	22.00
24040	200	310	109	-	-	-	-	30.50
24044	220	340	118	-	-	-	-	40.70
24048	240	360	118	-	-	-	-	39.00
24052	260	400	140	-	-	-	-	42.50
24056	280	420	140	-	-	-	-	64.90
24060	300	460	160	-	-	-	-	66.50
24064	320	480	160	-	-	-	-	106.00
24068	340	520	180	-	-	-	-	143.00
24072	360	540	180	-	-	-	-	149.00
24076	380	560	180	-	-	-	-	153.00
24080	400	600	200	-	-	-	-	202.00
24084	420	620	200	-	-	-	-	201.00
24088	440	650	212	-	-	-	-	249.00
24092	460	680	218	-	-	-	-	278.00
24096	480	700	218	-	-	-	-	288.00
240/500	500	720	218	-	-	-	-	295.00

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com

240/530	530	780	250	-	-	-	-	420.00
240/560	560	820	258	-	-	-	-	469.00
240/600	600	870	272	-	-	-	-	540.00
240/630	630	920	290	-	-	-	-	661.00

Bearing type	Internal Diameter	Outer Diameter	Width	Dynammic Load Rating	Static Load Rating	Limiting Speed		Weight
	d	D	B	Cr	Cor	Grease	Oil	
	(mm)	(mm)	(mm)	(kN)	(kN)	(r/min)	(r/min)	
24120	100	165	65	-	-	-	-	5.71
24122	110	180	69	-	-	-	-	5.70
24124	120	200	62	-	-	-	-	7.63
24126	130	210	80	-	-	-	-	12.30
24128	140	225	80	-	-	-	-	11.10
24130	150	250	100	-	-	-	-	19.90
24132	160	270	109	-	-	-	-	25.40
24134	170	280	109	-	-	-	-	23.40
24136	180	300	118	-	-	-	-	24.70
24138	190	320	128	-	-	-	-	33.00
24140	200	340	140	-	-	-	-	42.40
24144	220	370	150	-	-	-	-	65.30
24148	240	400	160	-	-	-	-	80.60
24152	260	440	180	-	-	-	-	115.00
24156	280	460	180	-	-	-	-	120.00
24160	280	460	180	-	-	-	-	120.00
24164	300	500	200	-	-	-	-	247.00
24168	340	580	243	-	-	-	-	266.00
24172	360	600	243	-	-	-	-	278.00
24176	380	620	243	-	-	-	-	290.00
24180	400	650	250	-	-	-	-	320.00
24184	420	700	280	-	-	-	-	443.00
24188	440	720	280	-	-	-	-	410.00
24192	460	760	300	-	-	-	-	578.00
24196	480	790	308	-	-	-	-	639.00
241/500	500	830	325	-	-	-	-	745.00
241/530	530	870	335	-	-	-	-	830.00
241/560	560	920	355	-	-	-	-	985.00
241/600	600	980	375	-	-	-	-	1079.00
241/630	630	1030	400	-	-	-	-	1410.00

瓦房店金锐轴承制造有限公司

Wafangdian Jinrui Bearing manufacturing Co., Ltd

✉ jerry@jrzc-bearing.com ☎ +86 17849695290

☎ +86 17849695290

🌐 www.jrzc-bearings.com